

# 20X DVD Multi Writer LS: AD-7201A



Read speed: 16x max. DVD and 48x max. CD

Write speed:

DVD +R: 20x max.	DVD-R: 20x max.
DVD +R9: 8x max.	DVD-R DL: 12x max.
DVD +RW: 8x max.	DVD-RW: 6x
CD-R: 48x max.	DVD-RAM: 12x max.

LightScribe laser labeling system

IDE/ATAPI interface with UltraDMA 66

(max. 66 MByte/sec transfer rate)

Tray load mechanism supporting horizontal and vertical use

Dust protected enclosure

Emergency eject



Specifications	20X DVD Multi Writer LS (AD-7201A)	
Transfer Rate read	<b>DVD</b>	<b>CD</b>
	16x CAV (max. 22000 kByte/s)	48x CAV (max. 7200 kByte/s)
Transfer Rate write	-R 20x CAV (max. 27500 kByte/s) -R DL 12x CAV (max. 16600 kByte/s) -RW 6x CLV (max. 8200 kByte/s) -RAM 12x ZCLV (max. 16600 kByte/s) +R 20x CAV (max. 27500 kByte/s) +R9 8x ZCLV (max. 11000 kByte/s) +RW 8x ZCLV (max. 11000 kByte/s)	48x CAV (max. 7200 kByte/s) /. 32x ZCLV (max. 4800 kByte/s) /. /. /. 160 ms
Access Time		140 ms
Mechanism	motorized tray load mechanism for horizontal and vertical use	
Interface	IDE / ATAPI	
Burst Transfer Rate	PIO mode 4 / Ultra DMA 66 mode 4	
Cache Memory	2 MByte	
Media/Modes supported	DVD-ROM, DVD-R(DL), DVD-RW, DVD+R(9), DVD+RW, DVD-Video, CD-ROM, CD-ROM XA, CD-Audio, CD Extra, CD Text, CD-I Ready, CD-Bridge, Photo-CD, VideoCD, Hybrid CD, LightScribe	
Writing methods	DAO (disc at once), SAO (session at once), TAO (track at once) with zero gap, variable or fixed packet, multisession	
Compatibility	MPC Level 3, MultiRead, PC2001, MS Vista™ compatible	
Available bezel colours	beige, black, silver	
Weight	0.69 kg	
Dimensions	148mm x 42mm x 170mm	